



P-YS600, 600 PSI, STAINLESS STEEL Y-STRAINER
INVESTMENT CASTING, SCREWED-IN CAP
 Thread Ends conform to ANSI B2.1, BS21 1973, DIN 259/2999



FEATURES :

- * **MATERIAL :**
 STAINLESS STEEL (ASTM-A351-CF8M)-AISI 316
 STAINLESS STEEL (ASTM-A351-CF8) - AISI 304
- * 100% air tested under water, open and closed
- * Standard screen 40 mesh

OPTIONS :

- * CF8M - Solution Heat Treatment
- * Screens 12 mesh, 20 mesh, etc...

SIZE	L	H	H1	D	A	B	KGS
1/4"	57	35	45	10.0	16	8	0.16
3/8"	57	35	45	10.0	16	8	0.15
1/2"	60	38	51	15.0	16	8	0.21
3/4"	69	42	55	20.0	16	8	0.28
1"	85	50	66	25.0	20.7	10	0.46
1-1/4"	99	55	73	32.0	25	12	0.67
1-1/2"	111	59	80	38.0	25	12	0.92
2"	137	73	100	51.0	32	12	1.44
2-1/2"	172	91.0	153	65	38	15	1.44
3"	205	110	173	80.0	38	15	1.44

6	GASKET	P.T.F.E
5	PLUG	316 : 304
4	PACKING	P.T.F.E
3	BONNET	316 : 304
2	SCREEN	316 : 304
1	BODY	CF8M, CF8
NO	PART	MATERIAL

