



NOTE : LUGGED BODY SHOWN , ALSO AVAILABLE IN WAFER BODY

SPECIFICATIONS		
DESCRIPTION	STANDARD	SPECIAL
BODY	CAST IRON	SS 316, DI, ALUBRONZE
DISC	STAINLESS STEEL 304 OR DUCTILE IRON (NICKEL PLATED)	SS 316, ALUBRONZE
SHAFT	STAINLESS STEEL 416	SS 316
SEAT	EPDM	BUNA-N, PTFE, VITON
OPERATOR	HAND LEVER	GEAR OPERATOR, ACTUATOR

All dimensions in inches

Size inch	A	B	C	D	E	F	G	H	J Tap	K	L	M	N 4 HOLES
2	10.75	6.34	3.15	1.65	10.63	4.75	2.00	4	5/8 UNC	0.48	0.45	2.25	0.26
2.5	11.65	6.89	3.50	1.76	10.63	5.50	2.50	4	5/8 UNC	0.48	0.45	2.25	0.26
3	12.13	7.13	3.74	1.78	10.63	6.00	3.00	4	5/8 UNC	0.48	0.45	2.25	0.26
4	13.62	7.87	4.49	2.05	10.63	7.50	4.00	8	5/8 UNC	0.60	0.57	2.75	0.41
5	14.65	8.39	5.00	2.14	12.32	8.50	5.00	8	3/4 UNC	0.74	0.71	2.75	0.41
6	15.63	8.90	5.47	2.20	12.32	9.50	6.00	8	3/4 UNC	0.74	0.71	2.75	0.41
8	18.90	10.24	6.89	2.39	14.25	11.75	8.00	8	3/4 UNC	0.87	0.84	3.50	0.56
10	21.26	11.50	7.99	2.58	14.25	14.25	10.00	12	7/8 UNC	1.12	1.09	3.50	0.56
12	24.57	13.27	9.53	3.03	19.50	17.00	12.00	12	7/8 UNC	1.24	1.21	4.25	0.56

Larger sizes available

- Heavy duty construction
- Blowout proof stem
- Bubble tight
- 10 Positions notch plate

**STYLE : BUTTERFLY VALVE,
CLASS 150 (200 WOG)**

Model : HS-BFV-LG

BFV-LG-1004-1