

DISTILLERY 150



Product Specification

Application

Distillery 150 is primarily used for liquid transfer. it is used to transfer high proof alcohol and other liquids (Example: Whiskey, Vodka) up to 100% per volume max. Alcohol Concentrate.

Packaging

Branding

CONTINENTAL DISTILLERY 150 PSI WP FDA 3-A & USDA ##### MADE IN CANADA

Construction Tube

- UHMWPE (FDA/USDA compliant)

Cover

- EPDM Rubber (wrapped impression)

Reinforcement

- Spiral-plied Fabrics with Double Galvanized Wire Helix

Temperature Range

- -40°F to 212°F (-40°C to 100°C)

Design Factor

- 4:1

DISTILLERY 150 #MAINIMAGE#

Order Codes: 549-683

ID	ID	OD	OD	Length	Color	Bend	Bend	Vacuum	Vacuum	WP	WP	Weight	Weight	Part
(in)	(mm)	(in)	(mm)	(ft)		Radius	Radius	HG	HG	(PSI)	(MPa)	(lbs/ft)	(kg/m)	Number
						(in.)	(mm)	(in.)	(mm)					
3/4	19.05	1.13	28.90	100	Gray	3	76	29	737	150	1.03	0.60	0.89	21104006
1	25.40	1.38	35.20	100	Gray	4	102	29	737	150	1.03	0.76	1.12	20866181
1-1/2	38.10	1.92	48.80	100	Gray	5	127	29	737	150	1.03	1.16	1.72	20866182
2	50.80	2.46	62.70	100	Gray	6	152	29	737	150	1.03	1.63	2.41	20866183
3	76.20	3.49	88.70	100	Gray	9	229	29	737	150	1.03	2.65	3.92	20866184
4	101.60	4.52	114.80	100	Gray	12	305	29	737	150	1.03	3.63	5.37	20866185