Haleson

FLEXLITE FFW FOODFLEX FDA

TECHNICAL DATA

Description	FDA & 3A Gray Smooth Food & Beverage Suction Hose
Application	Suction and discharge of fatty/oily and non-fatty/oily food and beverage applications where taste or aroma must not be affected.
Tube	Smooth White FDA compliant Nitrile, 3-A Sanitary Standards 18-07
Reinforcement	High Tensile Synthetic Textile
Cover	Smooth Wrapped Impression Gray Nitrile
Temperature Range	-22°F (-30°C) to 248°F (93°C) (Sterilization with steam +266°F (130°C))
Hose Assemblies	Made-to-order with quick turnaround. Suitable for hose reels. Available with NPT, Camlock, Tri-Clamp & Other Fittings.

FDA GRAY FOOD & BEVERAGE SUCTION HOSE

ITEM CODE	ID (in.)	OD (in.)	MAX. WP (PSI)	VACUUM (inHg)	MIN. BEND RADIUS (in.)	WEIGHT (lb./ft.)	FULL ROLL LENGTH (ft.)
FFW-050	1/2”	0.83	150	29	1.50	0.24	100
FFW-075	3/4”	1.14	150	29	2.25	0.40	100
FFW-100	1”	1.38	150	29	3.00	0.51	100
FFW-150	1-1/2”	1.97	150	29	3.50	0.92	100
FFW-200	2”	2.56	150	29	6.00	1.46	100
FFW-250	2-1/2”	3.03	150	29	7.50	1.66	100
FFW-300	3”	3.54	150	29	9.00	2.17	100

